


Introducing **SafeStop RackEnd Protector Double**, a flush-mounted safety barrier that protects racking, uprights and your facility. Its combined shock-absorbent materials give it the ability to slow and stop material handling equipment — ensuring the safety of your employees and the integrity of your concrete floors.

### HOW IT WORKS

SafeStop RackEnd Protector Double is packed full of innovative technology to safely stop heavy machinery. Upon impact, its reinforced uprights offer strength while its shock-absorbing rails flex to dissipate impact energy — keeping your operators, forklifts, and facility safe.










### IMPACT **TESTING**

Rigorous product testing at the highest standard.





90° 7,376 ft-lbs 10,000 J

45° 14,746 ft-lbs 19,995 J

30° 29,491 ft-lbs


39,990 J

#### WHAT DOES 7,376 FT LBS (10,000 J) MEAN TO YOU?




## MATERIAL PROPERTIES

#### **BARRIER DEFLECTION:**



	Working Temperatures	32°F-130°F (0°C-54°C)
$\triangle$	Toxicity	Not Hazardous



Flammability	Does Not Easily Ignite
REACH / RSCA / DSL	Compliant



# SAFESTOP RACKEND PROTECTOR DOUBLE ......

#### SafeStop RackEnd Protector Double

KIT NUMBER: RPD-K-120-307

Kit Includes: 2 Ends (RPD-C-END-307) 2 Rails (GB-C-RAL-307) Hardware

